



















































CASEMENT - SERIES CA740

SIZE CHART & STANDARD COLONIAL LITE CONFIGURATIONS

			X			XX			
COMMODITY	WINDOW WIDTH		19 ¹ / ₈	26 ¹ / ₂	37	37	53 ¹ / ₈	74	
	MASONRY OPENING*		19 ⁷ / ₈	27 ¹ / ₄	37 ³ / ₄	37 ³ / ₄	53 ⁷ / ₈	74 ³ / ₄	
	WOOD FRAME OPENING		18 ¹ / ₄	25 ⁵ / ₈	36 ¹ / ₈	36 ¹ / ₈	52 ¹ / ₄	73 ¹ / ₈	
MODULAR	26	26	25 ¹ / ₄	 12	 H32	 22	 22	 32	 D22
	38 ³ / ₈	38 ³ / ₈	37 ⁵ / ₈	 13	 H33	 23	 23	 33	 D23
	50 ⁵ / ₈	50 ⁵ / ₈	49 ⁷ / ₈	 14	 H34	 24	 24	 34	 D24
	63	63	62 ¹ / ₄	 15	 H35	 25	 25	 35	 D25
				X			XX		
WINDOW WIDTH		24	30	36	48	60	72		
MASONRY OPENING*		24 ³ / ₄	30 ³ / ₄	36 ³ / ₄	48 ³ / ₄	60 ³ / ₄	72 ³ / ₄		
WOOD FRAME OPENING		23 ¹ / ₈	29 ¹ / ₈	35 ¹ / ₈	47 ¹ / ₈	59 ¹ / ₈	71 ¹ / ₈		
WINDOW HEIGHT	24	24	23 ¹ / ₄	 2020	 2620	 3020	 4020	 5020	 6020
	36	36	35 ¹ / ₄	 2030	 2630	 3030	 4030	 5030	 6030
	48	48	47 ¹ / ₄	 2040	 2640	 3040	 4040	 5040	 6040
	60	60	59 ¹ / ₄	 2050	 2650	 3050	 4050	 5050	 6050
	72	72	71 ¹ / ₄	 2060	 2660				

DESIGN PRESSURE GUIDE

STYLE	TESTED PRESSURE	WATER-TESTED PRESSURE	TESTED SIZE	TYPE OF TEST
Casement (X)	+70/-90 psf	11.5 psf	37" x 63" or 32" x 72"	Miami-Dade Protocols TAS 201, 202, 203
Casement (XX)	+70/-90 psf	11.5 psf	74" x 63"	Miami-Dade Protocols TAS 201, 202, 203













* Masonry openings given assume precast sill and 1X buck.

CASEMENT - SERIES CA740

SIZE CHART & STANDARD COLONIAL LITE CONFIGURATIONS

















COMMODITY
XOX

WINDOW WIDTH	74	106 ³ / ₈	111
MASONRY OPENING*	74 ³ / ₄	107 ¹ / ₈	111 ³ / ₄
WOOD FRAME OPENING	73 ¹ / ₈	105 ¹ / ₂	110 ¹ / ₈

26	26	25 ¹ / ₂	 D22	 D32	 T22
38 ³ / ₈	38 ³ / ₈	37 ⁷ / ₈	 D23	 D33	 T23
50 ⁵ / ₈	50 ⁵ / ₈	50 ¹ / ₈	 D24	 D34	 T23
63	63	62 ¹ / ₂	 D25	 D35	 T25

MODULAR
XOX

WINDOW WIDTH	72	84	96	108
MASONRY OPENING*	72 ³ / ₄	84 ³ / ₄	96 ³ / ₄	108 ³ / ₄
WOOD FRAME OPENING	71 ¹ / ₈	83 ¹ / ₈	95 ¹ / ₈	107 ¹ / ₈

24	24	23 ¹ / ₄	 2020	 2620	 3020	 4020
36	36	35 ¹ / ₄	 2030	 2630	 3030	 4030
48	48	47 ¹ / ₄	 2040	 2640	 3040	 4040
60	60	59 ¹ / ₄	 2050	 2650	 3050	 4050

WINDOW HEIGHT
MASONRY OPENING*
WOOD FRAME OPENING

DESIGN PRESSURE GUIDE

STYLE	TESTED PRESSURE	WATER-TESTED PRESSURE	TESTED SIZE	TYPE OF TEST
-------	-----------------	-----------------------	-------------	--------------

* Masonry openings given assume precast sill and 1X buck.

Casement (XOX)	+70/-90 psf	11.5 psf	134" x 63"	Miami-Dade Protocols TAS 201, 202, 203
----------------	-------------	----------	------------	--